

SOD-323 Plastic-Encapsulate Diodes

ESD3Z24 Uni-direction ESD Protection Diode

DESCRIPTION


Unidirectional ElectroStatic Discharge (ESD) protection diode designed to protect one signal line from the damage caused by ESD and other transients.

FEATURES

- Uni-directional ESD protection
- Low reverse stand-off voltage: 24V
- Low reverse clamping voltage
- Low leakage current
- Fast response time
- JESD22-A114-B ESD Rating of class 3B per human body model
- IEC 61000-4-2 Level 4 ESD protection

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



MAXIMUM RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Limit	Unit
IEC 61000-4-2 ESD Voltage	$V_{ESD}^{(1)}$	± 25	kV
Air Model		± 25	
Contact Model		± 16	
Per Human Body Model		± 0.4	
ESD Voltage	$P_{PP}^{(2)}$	210	W
Peak Pulse Power	$I_{PP}^{(2)}$	2.5	A
Peak Pulse Current	T_L	260	°C
Lead Solder Temperature – Maximum (10 Second Duration)	T_j	150	°C
Junction Temperature	T_{stg}	-55 ~ +150	°C
Storage Temperature Range			

(1).Device stressed with ten non-repetitive ESD pulses.

(2).Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.

ELECTRICAL PARAMETER


Symbol	Parameter
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_R	Reverse Leakage Current @ V_{RWM}
V_{RWM}	Reverse Standoff Voltage
V_F	Forward Voltage@ I_F
I_F	Forward Current





**ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless otherwise noted)**

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse stand off voltage	$V_{RWM}^{(1)}$				24	V
Reverse leakage current	I_R	$V_{RWM}=24\text{V}$			1.0	μA
Breakdown voltage	$V_{(BR)}$	$I_T=1\text{mA}$	25		33	V
Clamping voltage	$V_C^{(2)}$	$I_{PP}=2.5\text{A}$			36	V
Junction capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		13		pF

(1).Other voltages available upon request.

(2).Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC61000-4-5



TYPICAL CHARACTERISTICS

PACKAGE OUTLINE**Plastic surface mounted package; 2 leads****SOD-323**