



MMBTRC116SS...MMBTRC122SS NPN Silicon Epitaxial Planar Transistor

for switching, interface circuit and drive circuit applications

Features

- With built-in bias resistors
- Simplify circuit design
- Reduce a quantity of parts and manufacturing process



1.Base 2.Emitter 3.Collector
SOT-23 Plastic Package

Resistor Values And Mark

Type	R1 (KΩ)	R2 (KΩ)	Marking Code
MMBTRC116SS	1	10	YN
MMBTRC117SS	2.2	2.2	YP
MMBTRC118SS	2.2	10	YR
MMBTRC119SS	4.7	10	YX
MMBTRC120SS	10	4.7	YY
MMBTRC121SS	47	10	YZ
MMBTRC122SS	100	100	ZA


Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Output Voltage	V_o	50	V
Input Voltage	V_i	10, - 5	V
		12, - 10	
		12, - 5	
		20, - 7	
		30, - 10	
		40, - 15	
		40, - 10	
Output Current	I_o	100	mA
Total Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_s	- 55 to + 150	°C

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_o = 5 \text{ V}$, $I_o = 5 \text{ mA}$ at $V_o = 5 \text{ V}$, $I_o = 20 \text{ mA}$ at $V_o = 5 \text{ V}$, $I_o = 10 \text{ mA}$ at $V_o = 5 \text{ V}$, $I_o = 10 \text{ mA}$ at $V_o = 5 \text{ V}$, $I_o = 10 \text{ mA}$ at $V_o = 5 \text{ V}$, $I_o = 5 \text{ mA}$ at $V_o = 5 \text{ V}$, $I_o = 5 \text{ mA}$	G_I	33	-	-	-
		20	-	-	-
		33	-	-	-
		30	-	-	-
		24	-	-	-
		33	-	-	-
		62	-	-	-
Output Cutoff Current at $V_o = 50 \text{ V}$	$I_{o(OFF)}$	-	-	500	nA
Input Current at $V_i = 5 \text{ V}$	I_I	-	-	7.2	mA
		-	-	3.8	
		-	-	3.8	
		-	-	1.8	
		-	-	0.88	
		-	-	0.16	
		-	-	0.15	
Output Voltage at $I_o = 10 \text{ mA}$, $I_I = 0.5 \text{ mA}$ at $I_o = 10 \text{ mA}$, $I_I = 0.5 \text{ mA}$ at $I_o = 10 \text{ mA}$, $I_I = 0.5 \text{ mA}$ at $I_o = 10 \text{ mA}$, $I_I = 0.5 \text{ mA}$ at $I_o = 10 \text{ mA}$, $I_I = 0.5 \text{ mA}$ at $I_o = 10 \text{ mA}$, $I_I = 0.5 \text{ mA}$ at $I_o = 5 \text{ mA}$, $I_I = 0.25 \text{ mA}$	$V_{o(ON)}$	-	-	0.3	V
		-	-	0.3	
		-	-	0.3	
		-	-	0.3	
		-	-	0.3	
		-	-	0.3	
		-	-	0.3	
Input Voltage (ON) at $V_o = 0.3 \text{ V}$, $I_o = 20 \text{ mA}$ at $V_o = 0.3 \text{ V}$, $I_o = 20 \text{ mA}$ at $V_o = 0.3 \text{ V}$, $I_o = 20 \text{ mA}$ at $V_o = 0.3 \text{ V}$, $I_o = 20 \text{ mA}$ at $V_o = 0.3 \text{ V}$, $I_o = 2 \text{ mA}$ at $V_o = 0.3 \text{ V}$, $I_o = 2 \text{ mA}$ at $V_o = 0.3 \text{ V}$, $I_o = 1 \text{ mA}$	$V_{I(ON)}$	-	-	3	V
		-	-	3	
		-	-	3	
		-	-	2.5	
		-	-	3	
		-	-	5	
		-	-	3	
Input Voltage (OFF) at $V_{CC} = 5 \text{ V}$, $I_o = 100 \mu\text{A}$	$V_{I(OFF)}$	0.3	-	-	V
		0.5	-	-	
		0.3	-	-	
		0.3	-	-	
		0.8	-	-	
		1	-	-	
		0.5	-	-	
Transition Frequency at $V_o = 10 \text{ V}$, $I_o = 5 \text{ mA}$	$f_T^{-1)}$	-	250	-	MHz

1) Characteristic of transistor only.

PACKAGE OUTLINE**Plastic surface mounted package; 3 leads****SOT-23**

UNIT	A	B	b_p	C	D	E	H_E	A_1	L_p
mm	1.40 0.95	2.04 1.78	0.50 0.35	0.19 0.08	3.10 2.70	1.65 1.20	3.00 2.20	0.100 0.013	0.50 0.20